

**PENDING CLAIMS AS AMENDED**

Please amend the claims as follows:

1. (Currently amended) An apparatus for providing electrical coupling, comprising:  
a motor having a hollow shaft extending there through and being capable of rotation, said shaft containing a conductor and being further capable of allowing electrical signals to pass there through and  
an antenna horn, being directly connected to said conductor, rotatable about said shaft, said shaft being disposed coaxially with said antenna horn on an axis of said antenna horn which extends through a plane in which said antenna horn is rotatable.
2. (Original) The apparatus of claim 1, wherein said shaft comprises a conductor, the shaft for conducting electrical signals through said motor.
3. (Original) The apparatus of claim 1, further comprising an electrical conductor located within said shaft for providing said electrical signals through said motor.
4. (Original) The apparatus of claim 3 wherein the electrical conductor comprises a coaxial cable.
5. (Original) The apparatus of claim 3 wherein the electrical conductor comprises a rotational coupler.
6. (Original) The apparatus of claim 3 wherein the electrical conductor comprises a wire.
7. (Original) The apparatus of claim 1 wherein the shaft comprises a waveguide.

8. (Original) The apparatus of claim 7, wherein the shaft additionally comprises a waveguide coupler.

9. (Previously presented) The apparatus of claim 3, further comprising a rotational coupler for coupling said electrical signals between a second conductor and the conductor.

10. (Previously presented) The apparatus of claim 3 further comprising a platform connected to the shaft wherein the conductor is fixed with respect to the shaft.

11. (Previously presented) The apparatus of claim 3, further comprising a platform connected to the shaft, wherein the conductor is affixed to the shaft and rotates therewith.

12. (Previously presented) The apparatus of claim 3, wherein the electrical conductor comprises an outer conductor, a dielectric, and a center conductor, wherein the dielectric and the center conductor are fixed, and the outer conductor is fixed to said shaft.

13. (Original) The apparatus of claim 1, wherein said shaft comprises:  
a dielectric material within said shaft and affixed thereto; and a center conductor within said dielectric material.